



## PGE20 SERIES

- Rugged, electronic gauge
- Gauge, compound, absolute and vacuum ranges from 5 psig to 15,000 psig
- 4-½ digit display with 0 to 100% bar graph
- 316L Stainless Steel wetted parts

### APPLICATIONS

- Hydraulics & pneumatics
- Leak detection
- Water management
- Hydrostatic pressure testing
- Burst testing
- Setting pressure switch set points

### MENU FUNCTIONS

- Min/Max Alarm (visual)
- Power off function
- Tare offset
- Battery status display
- Backlighting
- Optional data logger

### SPECIFICATIONS

<b>Pressure ranges</b>	Gauge, compound, absolute and vacuum ranges from 5 psig to 15,000 psig
<b>Accuracy</b>	±0.50% of full scale, including non-linearity, hysteresis, zero offset, and end point deviation per IEC 61298-2
<b>Temperature ranges</b>	Media -4 °F to 122 °F (-20 °C to 50 °C) Operating 14 °F to 122 °F (-10 °C to 50 °C) Storage 0 °F to 130 °F (-18 °C to 55 °C)
<b>Measuring element</b>	316L Stainless Steel
<b>Connection</b>	1/4" NPT Male, 316L Stainless Steel
<b>Case</b>	PBT with 30% glass fiber
<b>Display</b>	Resolution: 4-1/2 digits Back-lighting: activated via button Bar graph: 0 to 100% in 5% steps
<b>Power requirement</b>	3 x 1.5 V AA Alkaline batteries Typically > 4,000 hours
<b>Response time</b>	200 ms
<b>Proof pressure</b>	≤ 70 psi: 3 times full scale ≥ 100 to 7,500 psi: 2 times full scale > 7,500 psi: 1.43 times full scale
<b>Burst pressure</b>	≤ 70 psi: 4 times full scale ≥ 100 to 7,500 psi: 3 times full scale > 7,500 psi: 2 times full scale
<b>Programmable functions</b>	Adjustable through front key pad
<b>Measuring units</b>	psi, bar, mbar, MPa, kg/cm <sup>2</sup> and 1 user defined unit
<b>Environmental rating</b>	IP65
<b>Weight</b>	0.77 lb., including batteries

ORDERING INFORMATION								
SERIES	PGE20							
PRESSURE RANGES	15psiv	-15 psig to 0 psig	70psig	0 psig to 70 psig	1500psig	0 psig to 1,500 psig	5psia	0 psia to 5 psia
	15psic	-15 psig to 15 psig	100psig	0 psig to 100 psig	2000psig	0 psig to 2,000 psig	15psia	0 psia to 15 psia
	160psic	-15 psig to 160 psig	150psig	0 psig to 150 psig	3000psig	0 psig to 3,000 psig	30psia	0 psia to 30 psia
	200psic	-15 psig to 200 psig	200psig	0 psig to 200 psig	4000psig	0 psig to 4,000 psig	70psia	0 psia to 70 psia
	300psic	-15 psig to 300 psig	300psig	0 psig to 300 psig	5000psig	0 psig to 5,000 psig	120psia	0 psia to 120 psia
	600psic	-15 psig to 600 psig	400psig	0 psig to 400 psig	6000psig	0 psig to 6,000 psig	150psia	0 psia to 150 psia
	5psig	0 psig to 5 psig	500psig	0 psig to 500 psig	7500psig	0 psig to 7,500 psig	300psia	0 psia to 300 psia
	10psig	0 psig to 10 psig	600psig	0 psig to 600 psig	10000psig	0 psig to 10,000 psig	500psia	0 psia to 500 psia
	15psig	0 psig to 15 psig	750psig	0 psig to 750 psig	15000psig	0 psig to 15,000 psig		
	30psig	0 psig to 30 psig	1000psig	0 psig to 1,000 psig				
psiv = vacuum gauge		psic = compound pressure		psig = gauge pressure		psia = absolute pressure		Other ranges available on request
ACCURACIES	1 ±0.5% Full Scale		2 ±0.25% Full Scale*					
PROCESS CONNECTION	2 1/4" NPT male							
OPTIONS	DL Integrated Data Logger		RCP Rubber Case Protector		ST8 SS Threaded Orifice			

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

\* Includes additional units of measure, level, density and delay.

ORDERING INFORMATION - UNINSTALLED OPTIONS			
OPTIONS	CC Certified Calibration	PGE20-IC Interface Cable (Micro USB to USB cable 6 ft.)	PGE20-GC3 Gauge Carrying Case (3 gauge)
	PGE20-DL Field Activated Data Logger	PGE20-GC1 Gauge Carrying Case (1 gauge)	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

### EXAMPLE

Series ..... PGE20 Series  
 Pressure range ..... 0 psig to 1,500 psig  
 Accuracy ..... ±0.5% Full Scale  
 Process connection ..... 1/4" NPT Male  
 Options ..... Integrated Data Logger

PGE20 - 1500psig - 1 - 2 - DL

